EDCON-COMPONENTS











Applications

It is made with Epoxy cover, Suitable for use in humid locations such as bathroom and for use outdoors, for example on garden furniture or accentlighting on houses and buildings.

Features

Available in DC 12Volt or DC 24Volt maximum
Operating Temperature: -20°C ~ +50°C
Long Life span LED light, more than 50000hours
Viewing Angle of LED 120°
Available in Different White areas
2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 2,5mm

Technical Informations

Size of LED	5050	
LED per Meter	60PCS	
Voltage of LED Strip	24Volt	
Power of LED Strip	14,4Watt	
Emitting Color of LED Strip	Warm White 2700K	
Lumen per Meter	720~1080lm	
Protection Degree	IP65	

LED Flex-Strip LED-Size 5050


Part No.: **M33A8040**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	07.02.2012
APPD:	Schumi			FINISH	Jamv		Shee	et No.	1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











Ordering Informations

Part-No.

M33A8040

Special function	ROHS	Packing		
X	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel
Turicuori	N = NON ROHS	
	Conform	

LED Flex-Strip LED-Size 5050

Part No.: **M33A8040**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer: