EDCON-COMPONENTS











Applications

It is made with silicon for outside tube but it is hollow inside without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses and buildings..

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 4mm

Technical Informations

Size of LED	5050
LED per Meter	30PCS
Voltage of LED Strip	24Volt
Power of LED Strip	7,2Watt
Emitting Color of LED Strip	Red
Lumen per Meter	180lm
Protection Degree	IP67

LED Flex-Strip LED-Size 5050

Part No.: **M33A9043**


Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	07.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











Ordering Informations

Part-No.

M33A9043

Special function	ROHS	Packing		
V	D	TD		

V. Na anasial	R= ROHS	TR= Tape /
X= No special function	Conform	Reel
Turicuon	N= NON	
	ROHS	
	Conform	

LED Flex-Strip LED-Size 5050

Part No.: **M33A9043**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

email: info@edcon-components.com