
EDCON-COMPONENTS











Applications

It is made with silicon for outside tube but it is hollow inside without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses and buildings..

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 4mm

Technical Informations

Size of LED	5050		
LED per Meter	30PCS		
Voltage of LED Strip	24Volt		
Power of LED Strip	7,2Watt		
Emitting Color of LED Strip	Cool White 5500K		
Lumen per Meter	585lm		
Protection Degree	IP67		

LED Flex-Strip LED-Size 5050


Part No.: **M33A9049**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	07.02.2012	Customor
APPD:	Schumi			FINISH	Jamy			t No.	1 from 2	Customer:

email: info@edcon-components.com

EDCON-COMPONENTS











Ordering Informations

Part-No.

Special rontion ROHS Packing

X R TR

M33A9049

X= No special function	R= ROHS Conform	TR= Tape / Reel			
Turicuon	N = NON ROHS Conform				
	Contoni				

LED Flex-Strip LED-Size 5050

Part No.: **M33A9049**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

email: info@edcon-components.com