## **EDCON-COMPONENTS**











## **Applications**

It is made with silicon for outside tube but it is hollow inside without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses and buildings..

#### **Features**

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 4mm

### **Technical Informations**

Size of LED	5050
LED per Meter	30PCS
Voltage of LED Strip	24Volt
Power of LED Strip	7,2Watt
Emitting Color of LED Strip	Warm White 3000K
Lumen per Meter	540lm
Protection Degree	IP67

LED Flex-Strip LED-Size
5050

Part No.: **M33A9055** 

Customer:

DRW: CHKD Wilson MATL: Wilson TOLERANCE 07.02.2012 Mason DATE Jason APPD: **FINISH** Schumi Jamy Sheet No. 1 from 2

email: info@edcon-components.com

www.edcon-components.com

# **EDCON-COMPONENTS**











The Power of LED Light

## **Ordering Informations**

Part-No.
----------

M33A9055

Special function	ROHS	Packing		
Х	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel
Turiction	<b>N</b> = NON ROHS Conform	
		1

LED Flex-Strip LED-Size 5050

Part No.: **M33A9055** 

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer: