
## **EDCON-COMPONENTS**







A MEMBER OF EDCON-GROUP

The Power of LED Light

**Technical Informations** 

It is made with silicon for outside tube but it is hollow inside without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses and buildings..

## **Features**

Available in DC 12Volt or DC 24Volt maximum Operating Temperature: -20°C ~ +50°C Long Life span LED light, more than 50000hours Viewing Angle of LED 120° Available in Different White areas 2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length: 5000mm Width: 12mm Thickness: 4mm

| Size of LED          | 5050      |  |  |  |  |  |
|----------------------|-----------|--|--|--|--|--|
| LED per Meter        | 30PCS     |  |  |  |  |  |
| Voltage of LED Strip | 24Volt    |  |  |  |  |  |
| Power of LED Strip   | 7,2~8Watt |  |  |  |  |  |
|                      |           |  |  |  |  |  |
|                      |           |  |  |  |  |  |
| Protection Degree    | IP67      |  |  |  |  |  |

| Emitting Color of<br>LED Strip | Lumen per Meter |  |  |  |  |  |
|--------------------------------|-----------------|--|--|--|--|--|
| Red                            | 60lm            |  |  |  |  |  |
| Green                          | 120lm           |  |  |  |  |  |
| Blue                           | 75lm            |  |  |  |  |  |

|       |        |      |        |        |        |           |       | LED Flex-Strip LED-Size<br>5050 |            |            |          |
|-------|--------|------|--------|--------|--------|-----------|-------|---------------------------------|------------|------------|----------|
|       |        |      |        |        |        |           |       |                                 |            | Part No.:  | M33A9056 |
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason | DATE                            | 07.02.2012 | Customer:  |          |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Shee  | et No.                          | 1 from 2   | Cusionier. |          |

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com

## **EDCON-COMPONENTS**

REACH

Ø

RoHS Lead Free

D

Г

COMPONENTS A MEMBER OF EDCON-GROUP

 $\mathbf{N}$ 



The Power of LED Light

**Ordering Informations** 

| Part-No. |     | Special function | ROHS | Packing |  |  |
|----------|-----|------------------|------|---------|--|--|
|          | _   |                  |      |         |  |  |
| M33A9056 | - [ | Х                | R    | TR      |  |  |

| X= No special function | <b>R</b> = ROHS<br>Conform        | TR= Tape /<br>Reel |
|------------------------|-----------------------------------|--------------------|
|                        | <b>N</b> = NON<br>ROHS<br>Conform |                    |
|                        | Comon                             |                    |

|       |        |      |        |        |        |           | LED Flex-Strip LED-Size<br>5050 |      |            |           |          |
|-------|--------|------|--------|--------|--------|-----------|---------------------------------|------|------------|-----------|----------|
|       |        |      |        |        |        |           |                                 |      |            | Part No.: | M33A9056 |
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason                           | DATE | 07.02.2012 | Customer: |          |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. 2                     |      | 2 from 2   | Customer. |          |

www.edcon-components.com

Copyright by EDCON-COMPONENTS

email: info@edcon-components.com