
EDCON-COMPONENTS











Applications

It is made with silicon for outside tube but it is hollow inside without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses and buildings..

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 4mm

Technical Informations

Size of LED	5050				
LED per Meter	60PCS				
Voltage of LED Strip	24Volt				
Power of LED Strip	14,4Watt				
Emitting Color of LED Strip	Cool White 8000K				
Lumen per Meter	967~1170lm				
Protection Degree	IP67				

LED Flex-Strip LED-Size 5050


Part No.: **M33A9079**

Customer:

	DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	07.02.2012
ſ	APPD:	Schumi			FINISH	Jamv		Sheet No.		1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











Ordering Informations

Part-No.

Special **ROHS Packing** function Χ R TR

M33A9079

R= ROHS TR= Tape / X= No special Conform Reel function N= NON ROHS Conform

> **LED Flex-Strip LED-Size** 5050

Part No.: M33A9079

DRW: CHKD Wilson MATL: Wilson TOLERANCE Mason DATE 07.02.2012 Jason Customer: APPD: Schumi FINISH 2 from 2 Sheet No. Jamy

email: info@edcon-components.com