
EDCON-COMPONENTS











Applications

It is made with silicon for outside tube but it is hollow inside without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses and buildings..

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 4mm

Technical Informations

Size of LED	5050
LED per Meter	60PCS
Voltage of LED Strip	12Volt
Power of LED Strip	14,4Watt
Emitting Color of LED Strip	Red
Lumen per Meter	360lm
Protection Degree	IP67 UV

LED Flex-Strip LED-Size 5050


Part No.: **M33B1015**

Customer:

DRW: CHKD Wilson MATL: Wilson TOLERANCE 07.02.2012 Mason DATE Jason APPD: **FINISH** Schumi Jamy Sheet No. 1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











Ordering Informations

Part-No.

Special ROHS Packing

X R TR

M33B1015

X= No special function

R= ROHS Conform
Reel

N= NON
ROHS
Conform

LED Flex-Strip LED-Size 5050

Part No.: **M33B1015**

MATL: DRW: CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 Jason Customer: APPD: Schumi FINISH 2 from 2 Sheet No. Jamy

torrior.

email: info@edcon-components.com