EDCON-COMPONENTS











Applications

It is made with silicon for outside tube but it is hollow inside without any glue.

Suitable for use in humid locations such as bathrooms and for use outdoors, like on garden furniture or accent lighting on houses and buildings..

Features

Available in DC 12Volt or DC 24Volt maximum

Operating Temperature: -20°C ~ +50°C

Long Life span LED light, more than 50000hours

Viewing Angle of LED 120°

Available in Different White areas

2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip

Length: 5000mm Width: 12mm Thickness: 4mm

Technical Informations

Size of LED	5050	
LED per Meter	60PCS	
Voltage of LED Strip	24Volt	
Power of LED Strip	14,4Watt	
Emitting Color of LED Strip	Cool White 5500K	
Lumen per Meter	900~1170lm	
Protection Degree	IP67 UV	

LED Flex-Strip LED-Size 5050


Part No.: **M33B1035**

Customer:

DRW: CHKD Wilson MATL: Wilson TOLERANCE 07.02.2012 Mason DATE Jason APPD: **FINISH** Schumi Jamy Sheet No. 1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

Part-No.	
Part-No.	

M33B1035

Special function	ROHS	Packing		
Х	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel
Turicuon	N = NON ROHS	
	Conform	
		•

LED Flex-Strip LED-Size 5050

Part No.: **M33B1035**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 07.02.2012 APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

Customer: