

**Technical Specification**


**Features**

- Wire Wound Construction
- Polyolefin Shrink Tube
- Excellent heat resistance
- Excellent environmental characteristics
- High reliability

**Applications**

- Power Supplies
- SCR and TRIAC Controls
- RFI Suppression
- Filters
- Switching Regulators

**Dimensions**



Technical Dimensions			
D (mm)	L (mm)	E (mm)	F (mm)
11,5	12,0	10	6
d (mm)			
0,8			

**Electrical Characteristics**

**Technical Information**

Testing LCR Bridge, measured @ 1KHz 0,1V HP4284A  
 Equivalent acceptacle  
 RDC. QuadTech 1880 Milliohmmeter  
 IDC: Max. Lowers inductance by 10%  
 Operating Temperature: -55°C ~ +125°C  
 Shrink tube: Flame retardent UL type VW-1  
 Marking: Inductance and tolerance  
 Note: All specifications subject to change without notice.


Inductance	Inductance Code	IDC	DCR max.
680µH	681	0,420A	1,200Ω
Self-Resonant Frequency	L-Test Conditions		
796KHz	1KHz, 0,25V		

**THT Radial Power Choke**

Part No.: **S10R98**


Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	22.06.2018
APPD:	Join			FINISH	Shieh	Sheet	1 from 2



**Soldering Profile**

**TYPICAL WAVE SOLDER PROFILE FOR LEADED AND LEAD-FREE THROUGH-HOLE PACKAGES**



**Ordering Information**

Serie	Inductance	Tolerance	Lead Length	ROHS	Packing	
<b>S10R98</b>	<b>681</b>	<b>M</b>	<b>10</b>	<b>R</b>	<b>BU</b>	

<b>681</b> = 680µH	<b>M</b> = Tol. 20%	<b>10</b> = 10mm	<b>R</b> = ROHS conform	<b>BU</b> = Bulk Ware
	<b>K</b> = Tol. 10%		<b>N</b> =NON ROHS conform	<b>TY</b> = Tray Package

<b>THT Radial Power Choke</b>	
Part No.:	<b>S10R98</b>
Customer:	

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	22.06.2018
APPD:	Join			FINISH	Shieh	Sheet	2 from 2