



DATA SHEET

Mechanical Buzzer

Serie: Y11232

Mechanical Buzzer

Serie No.: **Y11232**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.06.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4


EDCON-COMPONENTS



Technical Specifications

Rated Voltage:	6,0 (Vp-p)
Operating Voltage:	5,0 ~ 7,0 (Vp-p)
Oscillation Frequency:	400 ±100 Hz
Current Consumption (mA/max) rated V.	25 mA max.
Sound Pressure Level :@ 10cm rated V.	80 min. dB
Operating Temperature:	.-20~ +60 °C
Storage Temperature:	.-30~ +70 °C
Dimensions:L x W x H	38,2x 26,0 x 15,2 mm
Termination Material / Plated	Brass/ Tin Plated
Housing:	ABS / Black
Termination:	Wire
Packing Unit: TRAY	100 PCS

Technical Dimensions (mm)



					Unspecified Tolerance (mm)					Mechanical Buzzer Part No.: Y11232 Customer:
					X.	X.x	X.xx	X.xxx	X.xxxx	
					0,35	0,25	0,2	0,15		
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.06.2018	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4		

EDCON-COMPONENTS



Ordering Informations

Serie	Wire Length	Wire Colour	Special function	ROHS	Packing Code					
Y11232	0100	A	N	R	TY					

		0= no special function	R= ROHS Conform	BU= Bulk Ware
0100= Customer spezified	A= Red/ Black wire		N= NON ROHS Conform	TU= TUBE Packing
XXXX= Customer spezified	X= Customer Specified			TY= TRAY Packing
				TR= TAPE REEL Packing
				IV= Individual Packing

Mechanical Buzzer

Part No.: Y11232


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.06.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)

**Mechanical Buzzer**Part No.: **Y11232**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.06.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	