


EDCON-COMPONENTS




SPECIFICATION:

Voltage Rating:	12VDC
Current Rating:	50mA
Mechanical Life:	200000 cycles
Contact Resistance:	100m Ω max. (initial)
Insulation Resistance:	100M Ω min. 500VDC
Dielectric Strenght:	250VAC/1min.
OperatingTemperature:	.-20°C ~ +70°C
Storage Temperature:	.-30°C ~ +80°C
Operating Force:	160gr $\pm$ 50gr
Travel:	0,15mm $\pm$ 0,1mm



Drawing



Circuit diagram





No	Part Name	Material	Finishing
1	Case	Liquid Crystal Polymer	UL94V-0 (Black)
2	Terminal	Brass	Ag Plate
3	Contact	Stainless Steel	Ag Plate
4	Dust Cover	PI Film	
5	Stem	Liquid Crystal Polymer	UL94V-0 (Black)
6	Cover	Stainless Steel	Ag Plate



SMT Tact Switch Frontside Sink Type

Part No.: **Q12150**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.07.2016	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 4		



SMT Tact Switch Frontside Sink Type

Part No.: **Q12150**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.07.2016
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4	



Ordering Informations

Serie	Total length w. Body	Special function	Operating Force	Polarisation Peg	Electrical life	Special function	ROHS	Packing		
Q12150	026	N	161	N	104	N	R	TR		

026 = 2,6mm	N = No special function	161 = 160gr	N = without Peg	104 = 100000 Cycles	N = No special function	N = Non ROHS	TR = Tape/Reel Packing
						R = ROHS conform	TU = Tube Packing
							BU = Bulk Ware

**SMT Tact Switch
Frontside Sink Type**
Part No.: **Q12150**


Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.07.2016
APPD:	Schumi			FINISH	Jamy		Sheet No.	3 from 4	



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)


**SMT Tact Switch
Frontside Sink Type**

 Part No.: **Q12150**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.07.2016
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	