


# EDCON-COMPONENTS



## Technical Discription

## Drawing

### 1 Material:

Material Body:	C2700
Gold Plated:	16-20µm
Nickel:	60-120µm
Material Needle:	C3604
Gold Plated:	4-8µm
Nickel:	60-120µm
Spring:	SUS304
Body:	PA46

### 2 Mechanical Properties

Pitch:	2,54mm
Working height:	5,8-6,1mm
Elastic:	100 ±20gr

Lifetime: more than 10000 times

### 3 Electrical Performance:

#### 4 Isolation Resistance:




Withstanding Voltage:	500M Ohm min.
Max. Rated Voltage:	500VAC/DC
Contact Resistance:	36VDC dynamic range of work with impedance less than <30m Ohm

Rated current: 2,5A

### 5 Packing Specification:

Max. Soldering Temperature: 260°C

Operating Temperature: -40°C to +85°C



Tolerance			
0.	0.0	0.00	0.000
± -	± 0,30	± 0,15	± -
TOLERANCE	Mason	DATE	06.12.2017
APPD:	Sheet No.	1 from 3	


**8 POGO PIN with Plastic**

Part No.: **TA23B9008**


Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	FINISH	Jamy
------	-------	------	--------	-------	--------	--------	------

# EDCON-COMPONENTS



PCB Layout ( mm)



## Ordering Informations


Serie	Number of Position	Material Body	Material Needle	Contact Plat. Body	Contact Plat. Needle	Spezial Function	ROHS	Packing		
TA23B9008	08	A	A	G0	G0	N	R	BU		

08= Position	A= Material C3604	A= Material C3604	G0= Gold Flash <16-20µinch	G0= Gold Flash 4-8µinch	N= No function	R= ROHS Conform	BU= Bulk-Ware Standard
	B= Material C2700	B= Material C2700					
			N0= Nickel 60-120µinch	N0= Nickel 60-120µinch			TR= Tape Reel

**8 POGO PIN with Plastic**

Part No.: **TA23B9008**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.12.2017	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 3		



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



<b>8 POGO PIN with Plastic</b>	
Part No.:	<b>TA23B9008</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.12.2017
APPD:	Schumi			FINISH	Jamy		Sheet No.	3 from 3	