





Technical Specification

Insulator:	Black glass filled polyester PPS-GF-30-FR
Flammability:	UL 94V-0
Sleeve:	Brass CuZn 36Pb3 (36000)
Contact Clip (6finger):	Beryllium Copper (C17200)
Forces:	polished steel gauge(Ø)0,76mm
.-Insertion:	1,2N typ.
.-Withdrawel:	0,6N typ.
Mechanical Life:	min 500 cycles
Rated Current:	3A
Contact Resistance:	max. 10m Ohm
Dielectric Strength:	min 1000V rms
Minimal position of deliver:	4
Maximal position of deliver:	80

PCB Layout



Technical Drawing



Ordering Information

Serie	No. of Pos.	Solder Pin Plating	Special function	ROHS	Packing
T40203	04	A	0	R	B1

04 ~80	A= Tin 150µ" (Standard)	0= no special function	R= ROHS conform	B1= Bulk 100PCS
	B= Tin 200µ"		N= NON ROHS conform	
	C= GF			
	D= Gold 2µ"			
	E= Gold 3µ"			
	F= Gold 10µ"			
	G= Gold 15µ"			
	H=Special			

**Machined Contact Pitch
2,54mm**

Part No.: **T40203**

Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	21.07.2017
APPD:	Join			FINISH	Shieh	Sheet	1 from 1