




Technical Specification

Insulator:	Black glass filled polyester PPS-GF-30-FR
Flammability:	UL 94V-0
Sleeve:	Brass CuZn 36Pb3 (36000)
Contact Clip (6finger):	Beryllium Copper (C17200)
Forces:	polished steel gauge(Ø)0,76mm
.-Insertion:	1,2N typ.
.-Withdrawel:	0,6N typ.
Mechanical Life:	min 500 cycles
Rated Current:	3A
Contact Resistance:	max. 4m Ohm
Dielectric Strength:	min 1000V rms
Mating with pin:	Ø 0,66mm
Maximal position of deliver:	2
Maximal position of deliver:	40

Technical Drawing



PCB Layout



Ordering Information

Serie	No. of Pos.	Solder Pin Plating	Inner Clip Plating	ROHS	Packing
T40288	02	A	3	R	B1

02 ~40	A= Tin 150µ" (Standard)	1= Tin 150µ" 2= Tin 200µ"	R= ROHS conform	B1= Bulk 100PCS
	B= Tin 200µ"	3= GF (Standard)	N= NON ROHS conform	
	C= GF	4= Gold 2µ"		
	D= Gold 2µ"	5= Gold 3µ"		
	E= Gold 3µ"	6= Gold 10µ"		
	F= Gold 10µ"	7= Gold 15µ"		
	G= Gold 15µ"	8= Special		
	H= Special			

**Machined Contact Pitch
2,54mm**

Part No.: **T40288**

Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	22.07.2017
APPD:	Join			FINISH	Shieh	Sheet	1 from 1