

# EDCON-COMPONENTS



## Technical Description

Curent Rating:	14A AC/DC at 16AWG
Contact Resistance:	15mΩ max.
Withstanding Voltage:	1800VAC/ DC
Insulation Resistance:	1000MΩ Min
Operating Temperature:	.-40°C to + 105°C
Contact Material:	Brass
Contact Plating:	Matte SN over Ni
Insulator Material:	LCP + 30%G.F UL94V-0
Available Pos.	2 to 8Pos

## Drawing

## PCB Layout (mm)

						<b>Wire to Board Connector (Housing) Dual Row</b>					
				Tolerance	x	x.x	x.xx	x.xxx	Angle	Part No.:	<b>T68H011</b>
DRW:	Jason	CHKD	Wilson	MATL:	±	±0,40	±0,25	±0,15	± 3°	Customer:	
APPD:	Schumi			FINISH	Wilson	Jamy	Mason	DATE	06.06.2021		
							Sheet No.		1 from 3		



# EDCON-COMPONENTS



## Ordering Informations

Serie	No. Of Position	Contact Plating	Contact Material	Color of Body	Key Code	Special Function	ROHS	Packing		
-------	-----------------	-----------------	------------------	---------------	----------	------------------	------	---------	--	--

<b>T68H011</b>	<b>04</b>	<b>TN</b>	<b>BR</b>	<b>BK</b>	<b>L</b>	<b>N</b>	<b>R</b>	<b>BU</b>		
----------------	-----------	-----------	-----------	-----------	----------	----------	----------	-----------	--	--

<b>04=</b> 2x2Pos.	<b>TN=</b> tinned	<b>BR=</b> Brass		<b>L=</b> Left Side	<b>N=</b> No Function	<b>R=</b> ROHS Conform	<b>BU=</b> Bulk-Ware
2x2 ~ 2x12Pos.			<b>BK=</b> Black	<b>R=</b> Right Side		<b>N=</b> NON ROHS Conform	<b>TU=</b> Tube Packing
						<b>TC=</b> Tube w. Cap Packing	
						<b>TR=</b> Tape/Reel Packing w. Cap w. needed	
						<b>IV=</b> Individual Packing	
			<b>NA=</b> Nature				

<b>Wire to Board Connector (Housing) Dual Row</b>	
Part No.:	<b>T68H011</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.06.2021
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3