


EDCON-COMPONENTS



Technical Description

Material:

Insulator: PBT
 Flammability Rating: UL94-V0
 Max. Temperature: 220°C / 10Sec.
 Colour Housing: Black
 Shell: Steel Tin Plated
 Environmental:
 Operating Temperature: -55°C to + 105°C

Electrical

Current Rating: max. 3A
 Working Voltage: 125VAC
 Insulation Resistance: >5000MΩ
 Dielectric Withst. Voltage: 1000V AC/Min

Dimension

50P	mm
A	
B	
C	
D	
E	
F	


Drawing

**D-SUB-Crimp-Terminal
Housing Male**

Part No.: **T24E5005**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2022	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 2		

EDCON-COMPONENTS



Ordering Informations

Serie	No of contacts	Type	Shell Surface	Special	ROHS	Packing
T24E5005	50	M	TN	00	R	BU
	50= No of Position	M= Male	TN= tinned Shell	00= No function	R= ROHS Conform N= NON ROHS Conform	BU= Bulk-Ware IV= Individual Package

D-SUB-Crimp-Terminal Housing Male	
Part No.:	T24E5005
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	08.02.2022
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 2	