



## Technical Specification

### Features

Closed magnetic circuit structure allows high density mounting on a PCB board, mounting while preventing crosswalk.

Extremely high reliability due to entirely monolithic construction.

Low DC resistance structure of electronic to prevent wasteful electric power consumption.

High current application rating look at range.

### Dimensions



| Chip Dimensions |          | Size Code | Size Dimension |
|-----------------|----------|-----------|----------------|
|                 |          | 0805      | 2012           |
| L (mm)          | W (mm)   | T (mm)    | RW (mm)        |
| 2,0±0,3-01      | 1,25±0,2 | 0,05      | 0,5±0,3        |

## Specifications / Test conditions

|                               | Test-Cond. | Min            | Typ.           | Max | Unit | Tol. % | Order Code |
|-------------------------------|------------|----------------|----------------|-----|------|--------|------------|
| Impedance: ( Z )              | 100 Mhz    |                | 300            |     | Ω    | 25     | 301        |
| Impedance: ( Z )              | 0 Ghz      |                | 0              |     | Ω    | 0      |            |
| DC-Resistance: (RDC)          |            | --             | 0,05           | --  | Ω    |        |            |
| Rated Current: ( IDC )        |            | --             | 3000           | --  | mA   |        | 302A       |
| Operating Temperature: ( °C ) |            | -55°C ~ +125°C |                |     |      |        |            |
| Tolerance Code:               |            | N              | Material Code: |     | A    |        |            |

### Typical Impedance v.s. Frequency Curve:

### Circuit



### High Current for DC-Power Line Chip Beads

Serie No.: G12047-301-302A

Customer:

### FREQUENCY (Mhz)

|       |        |      |       |  |        |       |            |
|-------|--------|------|-------|--|--------|-------|------------|
| DRW:  | Johnny | CHKD | Carlo |  | Wor    | DATE  | 27.08.2024 |
| APPD: | Elva   |      |       |  | Vienna | Sheet | 1 from 2   |

Copyright by EDCON S.Tiede

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)



### Soldering Profile for Lead Soldering

### Soldering Profile for Lead Free Soldering



### Ordering Information

| Serie | Tolerance | Special | ROHS | Packing |
|-------|-----------|---------|------|---------|
|-------|-----------|---------|------|---------|

|                 |   |   |   |    |
|-----------------|---|---|---|----|
| G12047-301-302A | N | X | R | TR |
|-----------------|---|---|---|----|

|                  |                        |                    |                                |
|------------------|------------------------|--------------------|--------------------------------|
| N= Tolerance 25% | X= No special function | R= ROHS conform    | BU= Bulk Ware<br>TR= Tape/Reel |
|                  |                        | N=NON ROHS conform |                                |

### High Current for DC-Power Line Chip Beads

Serie No.: G12047-301-302A

Customer:

|       |        |      |       |  |        |       |            |
|-------|--------|------|-------|--|--------|-------|------------|
| DRW:  | Johnny | CHKD | Carlo |  | Wor    | DATE  | 27.08.2024 |
| APPD: | Elva   |      |       |  | Vienna | Sheet | 2 from 2   |

Copyright by EDCON S.Tiede

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)