EDCON COMPONENTS
A MEMBER OF EDCON-GROUP

Technical Specification

Features

Closed magnetic circuit structure allows high density mounting an a pcb board, mounting while preventing crosswalk.
Extremly high reliability due to entirely monolithic construction.
Low DC resistance structure of electronic to prevent wasteful electric power consumption.
High current application rating look at range.

Dimensions



Chip Dimensions	Size Code	Size Dimension
	0201	0603

L (mm)	W (mm)	T (mm)	RW (mm)
0,6±0,05	0,3±0,05	0,45	0,15±0,05

Specifications / Test conditions

	Test-Cond.		Min	Typ.	Max	Unit	Tol.%	Order Code
Impedance: (Z)	100	Mhz		120		Ω	25	121
Impedance: (Z)	0	Ghz		0		Ω	0	
DC-Resistance: (RDC)			--	0,45	--	Ω		
Rated Current: (IDC)			--	200	--	mA		201A
Operating Temperature: (°C)		.-55°C ~ +125°C						
Tolerance Code:	N	Material Code:		A				

Typical Impedance v.s. Frequency Curve:

FREQUENCY (Mhz)

Circuit



Multilayer Chip Suppressors Chip Beads

Serie No.: G12052-121-201A

Customer:

DRW:	Johnny	CHKD	Carlo		Wor	DATE	27.08.2024
APPD:	Elva				Vienna	Sheet	1 from 2

Copyright by EDCON S.Tiede

EDCON COMPONENTS
A MEMBER OF EDCON-GROUP

Soldering Profile for Lead Soldering



Soldering Profile for Lead Free Soldering



Ordering Information

Serie	Tolerance	Special	ROHS	Packing
G12052-121-201A	N	X	R	TR

N= Tolerance 25%	**X**= No special function	**R=** ROHS conform	**BU=** Bulk Ware
		N=NON ROHS conform	**TR=** Tape/Reel

Multilayer Chip Suppressors Chip Beads

Serie No.: **G12052-121-201A**

Customer:

DRW:	Johnny	CHKD	Carlo		Wor	DATE	27.08.2024
APPD:	Elva				Vienna	Sheet	2 from 2

Copyright by EDCON S.Tiede

www.edcon-components.com email: info@edcon-components.com