

**Type Code**


**CPB24B12-3.6:**

Chinasound Piezo Buzzer 23.5(<24mm) diameter, type B (=9.5mm height), 12VDC rated voltage -, 3.6KHz resonant frequency

**Picture**



**Characteristics**



**Technical Terms**

Type		<b>CPB24B12-3.6</b>
Rated Voltage	(VDC)	12
Operating Voltage	(VDC)	3~20
Rated Current at 12VDC	(mA)	10 max.
Sound Output at 12VDC, 10cm	(dB)	90dB min.
Resonant Frequency	(Hz)	3600+/-500
Tone		Continuous
Operating Temperature	(°C)	-20~+70
Storage Temperature	(°C)	-40~+85
Weight	(g)	2.8

**Reliability**

Life Test	Operate the part at 12VDC in room temperature continuously for 1000 hours.
Operating Temperature	Driving from -20 °C to +70 °C within 30 minutes for 2 cycles
High Temperature	+85 °C+/-2 °C, 120hrs
Low Temperature	-40 °C+/-2 °C, 120hrs
Humidity	+60 °C+/-2 °C, 90~95%RH, 120hrs
Thermal Shock	-40 °C+/-2 °C, 1hr→+20 °C,5min,→+85 °C+/-2 °C, 1hr→+20 °C,5min, 5 cycles
Shock	980m/s <sup>2</sup> (=100g) shock for each 3 mutually perpendicular directions to each of 3 times by half sine wave
Vibration	1.5mm with 10 to 50Hz of vibration frequency to each of 3 perpendicular direction for 2 hrs
Drop Test	Dropped naturally from 700mm height onto the surface of 10mm thick wooden board. 2 directions - upper and side of the part are to be applied.

All specifications must be satisfied after the test (Recovery:2 to 4 hrs of recovery under the standard condition after the removal from test chamber)

**Dimensions (Unit:mm)**

