


EDCON-COMPONENTS



SPECIFICATION:

Current Rating:	0,3 Ampere
DC- Voltage	50 VDC
Dielectric Withstanding:	AC 500V
Operating Temperature:	.-40°C to +105°C
Function:	1P2T
Timing:	Non-Shorting / Shorting
Contact Resistance:	30m Ω max.
Insulation Resistance:	100M Ω min at 500VDC
Life Test:	10000 cycles

Knop Type




Type A



Type B

Material of Switch

Board:	Phenolic Resin (Nature)
Contact Clip:	PBS Strip (Nature)
Frame:	Iron Strip (Ni plated)
Terminal:	Brass Strip (Ag Plated)
Knob:	POM (Black)




Circuit

THT Slide-Switch




Part No.: **Q13085**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	19.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4



Drawing




Special function A

Type	M	A
Type 1	2	2
Type 2	3,8	1,8
Type 3	4	1,5

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	19.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

THT Slide-SwitchPart No.: **Q13085**

Customer:



Ordering Informations

Serie	Knob Type	Knob Length	Circuit	Special function A	Special function B	ROHS	Packing			
Q13085	A	02	N	1	N	R	BU			


A= Type A	02= Length L=2,0mm	N= Non Shorting	1= Type 1	N= No function	R= ROHS Conform	BU= BULK- WARE
	L=2 ~ 15mm	S= Shorting	2= Type 2		N= NON ROHS Conform	IV= Individual Package
			3= Type 3			

THT Slide-Switch

Part No.: **Q13085**


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	19.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4

Customer:
email: info@edcon-components.com



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



THT Slide-Switch

Part No.: **Q13085**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	19.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	