



## Technical Specification


### Features

Ferrite Core  
Wire Wound construction  
Heat Resistant epoxy molded resin  
High reliability Ideal for automatic insertion  
Small Size  
Tolerance 10% is standard tighter tolerance available

### Applications

VCRs, PDP LCD, TV set  
Automotive Systms  
Computer Peripheral Equipment  
GPS, DC/DC Converter,  
XDSL Modem  
Electronic Games  
Mobile Communications Equipment  
General Electronic Applications

### Dimensions



## Electrical Characteristics

### Technical Information

Inductance Testing: HP4284A, HP 4285A equivalent  
RDC: Quad Tech 1880 Milliohm meter  
Q-HP4342A  
SRF-HP4191A or HP4194A  
Rated Current L value drop 10% typ.at Idc against  
ist initial value.  
Temperature rise: 40 Max. Reference ambient temper.  
Solderability: 75° of the lead wire shall be covered  
SolderingMethods: Wave ; Reflow  
Operating Temperature: -25°C ~ +85°C  
Storage Temperature: -55°C ~ +105°C  
Terminal bending strength: 24,5N min.  
Moisture resistance: L/L 10% Q/Q 25%

| Inductance | Inductance Code | IDC    | DCR max. |
|------------|-----------------|--------|----------|
| 120μH      | 121             | 0,140A | 5,200Ω   |

|  | Q min. | L-Test Freq. | SRF    |
|--|--------|--------------|--------|
|  | 65     | 0,79MHz      | 8,0MHz |

### THT AXIAL MOLDED Choke

Part No.: **S10A03**

Customer:


|       |       |      |     |        |      |       |            |
|-------|-------|------|-----|--------|------|-------|------------|
| DRW:  | James | CHKD | Jim | MATL:  | Wim  | DATE  | 05.07.2007 |
| APPD: | Sarah |      |     | FINISH | Jeff | Sheet | 1 from 2   |

Copyright by EDCON-COMPONENTS H.Schmitt



## Soldering Profile

### Classification Reflow Profile (JEDEC J-STD-020C)



## Ordering Information

| Serie         | Inductance | Tolerance | Function | ROHS     | Packing   |  |
|---------------|------------|-----------|----------|----------|-----------|--|
| <b>S10A03</b> | <b>121</b> | <b>K</b>  | <b>N</b> | <b>R</b> | <b>TR</b> |  |

|                   |                    |                       |                            |                              |
|-------------------|--------------------|-----------------------|----------------------------|------------------------------|
| <b>121=</b> 120µH | <b>K=</b> Tol. 10% | <b>N=</b> No function | <b>R=</b> ROHS conform     | <b>BU=</b> Bulk Ware         |
|                   | <b>J=</b> Tol. 5%  |                       | <b>N=</b> NON ROHS conform | <b>TR=</b> Tape Reel Package |

### THT AXIAL MOLDED Choke

Part No.: **S10A03**

Customer:

|       |       |      |     |        |      |       |            |
|-------|-------|------|-----|--------|------|-------|------------|
| DRW:  | James | CHKD | Jim | MATL:  | Wim  | DATE  | 05.07.2007 |
| APPD: | Sarah |      |     | FINISH | Jeff | Sheet | 2 from 2   |

