



Technical Specification



Features

Magnetic Core
Wire Wound construction
Heat Resistant epoxy molded resin
High reliability Ideal for automatic insertion
Small Size
Tolerance 10% is standard tighter tolerance available


Applications

VCRs, PDP LCD, TV set
Automotive Systms
Computer Peripheral Equipment
GPS, DC/DC Converter,
XDSL Modem
Electronic Games
Mobile Communikations Equipment
General Electronic Applications

Dimensions



TB26



TB52

Electrical Characteristics

Technical Information

Inductance Testing: HP4284A, HP 4285A equivalent
RDC: Quad Tech 1880 Milliohm meter
Q-HP4342A
SRF-HP4191A or HP4194A
Rated Current L value drop 10% typ.at Idc against
ist initial value.
Temperature rise: 40 Max. Reference ambient temper.
Solderability: 75° of the lead wire shall be covered
SolderingMethods: Wave ; Reflow
Operating Temperature: -25°C ~ +85°C
Storage Temperature: -55°C ~ +105°C
Terminal bending strength: 24,5N min.
Moisture resistance: L/L 10% Q/Q 25%

Inductance	Inductance Code	IDC	DCR max.
10μH	100	0,160A	2,500Ω

	Q min.	L-Test Freq.	SRF
	50	7,96MHz	21MHz

THT AXIAL Standard Coated Inductors

Part No.: **S10A14**

Customer:


DRW:	James	CHKD	Jim	MATL:	Wim	DATE	06.08.2008
APPD:	Sarah			FINISH	Jeff	Sheet	1 from 2

Copyright by EDCON-COMPONENTS H.Schmitt



Soldering Profile

Classification Reflow Profile (JEDEC J-STD-020C)



Ordering Information

Serie	Inductance	Tolerance	Function	ROHS	Packing	
-------	------------	-----------	----------	------	---------	--

S10A14	100	K	N	R	TB52	
---------------	------------	----------	----------	----------	-------------	--

100 = 10µH	K = Tol. 10%	N = No function	R = ROHS conform	BU = Bulk Ware
	J = Tol. 5%		N =NON ROHS conform	TB26 = Tape Box Package
				TB52 = Tape Box Package

THT AXIAL Standard Coated Inductors

Part No.: **S10A14**

Customer:

DRW:	James	CHKD	Jim	MATL:	Wim	DATE	06.08.2008
APPD:	Sarah			FINISH	Jeff	Sheet	2 from 2

