EDCON-COMPONENTS











Applications

It is made with Epxy Cove, Suitable for use in humid locations such as bathrooms and for use outdoors for example on garden funiture or accent lightinh on house and buildings.

Features

Available in DC 12Volt or DC 24Volt maximum
Operating Temperature: -20°C ~ +50°C
Long Life span LED light, more than 50000hours
Viewing Angle of LED 120°
Available in Different White areas
2400K, 2700K, 3000K, 4200K, 5500K, 6000K, 8000K, 10000K

Available in color, Red, Green, Blue, Yellow, Pink,

Dimension of Flex-LED-Strip Length= 5000mm Width= 10mm Thickness: 2,5mm

Technical Informations

Size of LED	3528	
LED per Meter	60PCS	
Voltage of LED Strip	24Volt	
Power of LED Strip	4,8Watt	
Emitting Color of LED Strip	Warm White 2400K	
Lumen per Meter	360lm	
Protection Degree	IP65	

LED Flex-Strip LED-Size 3528

Part No.: **M33A2076**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.02.2012
APPD:	Schumi			FINISH	Jamy		Shee	t No.	1 from 2

email: info@edcon-components.com

EDCON-COMPONENTS











The Power of LED Light

Ordering Informations

Part-No.

M33A2076

Special function	ROHS	Packing		
Χ	R	TR		

X= No special function	R= ROHS Conform	TR= Tape / Reel		
Turiction	N = NON ROHS Conform			

LED Flex-Strip LED-Size 3528

Part No.: **M33A2076**

MATL: DRW: Jason CHKD Wilson Wilson TOLERANCE Mason DATE 06.02.2012 Customer: APPD: Schumi FINISH Sheet No. 2 from 2 Jamy

oner.